#### \*All Material Being Used Shall Conform w/OMWD's Standard Specifications

Project \_\_\_\_\_\_

## PLEASE INDICATE WHICH PRODUCT YOU ARE USING BY PLACING AN "X" ON THE APPROPRIATE LINE TO THE RIGHT OF EACH MANUFACTURER

| Item   | Description   | Std Spec                | Manufacturer   |
|--|---|-------------------------|--|
| AIR/VACUUM VALVE<br>ENCLOSURE<br>*must be accompanied by<br>a shop drawing | 2 Piece Assembly with Bolt Down Base and<br>Removable Cover, Polyethylene Material,<br>Sandstone Color with Identification Band,<br>OSHA Blue for WATER, OSHA Purple for<br>Recycled Water<br>1424 for 1"<br>1830 for 2"<br>2436 for 3" | <u>Section</u><br>15092 | VCAS-1424-SM w/tape & screen<br>VCAS-1830-SM w/tape & screen<br>VCAS-2436-SM w/tape & screen<br>RCW<br>Potable |
| ANGLE METER STOP,<br>QUICK JOINT X<br>METER NUT                            | 1" Bronze Angle Meter Stop (Ball Valve)<br>with 90 Degree Lockwing, Inlet Quick Joint<br>for Copper Water Tube x Meter Swivel Nut<br>Outlet   | 15081                   | Ford BA43-444W-Q-NL<br>Jones - J1963WSG<br>McDonald 74602BQ<br>Mueller - B24258                                |
| ANGLE METER STOP,<br>QUICK JOINT X<br>METER FLANGE                         | 1-1/2", 2" Bronze Angle Meter Stop (Ball<br>Valve) with 90 Degree Lockwing, Inlet<br>Quick Joint for Copper Water Tube x Meter<br>Flange Outlet   | 15081                   | Ford BFA43-777W-Q-NL          Jones - J1975WSG          McDonald 74602BQ          Mueller - B24276             |
| ANGLE VALVE  | Bronze Angle Valve, 2" and Smaller<br>300 PSI Rated, Female Threaded Ends   | 15080                   | Nibco T-375-B            Jones J-380   |
| ANGLE VALVE<br>HYDRANT HEAD  | Bronze, Angle Design, 300 PSI Rated, 4"<br>Inlet Female IPT, 2-1/2" Outlet National<br>Standard Hose Thread, Cap and Chain  | 15080                   | Jones J-344HP  |
| ANODE, MAGNESIUM<br>*must be accompanied by<br>a shop drawing              | High or Standard Potential Anode with a<br>Galvanized Steel Core Encased in a Square<br>Magnesium Alloy Ingot Pre-Packaged in a<br>Permeable Cotton Cloth Bag. Provide Ingot<br>Weight as Specified on the Approved Plans               | 13110                   | Corrpro<br>Corrosion Control Products<br>Farwest<br>Calpico  |
| ANODE, ZINC  | Each Zinc Anode shall be Prepackaged in a<br>Permeable Cloth Bag and shall Weigh 30<br>Pounds   | 13110                   | Corrpro<br>Corrosion Control Products<br>Farwest<br>Calpico  |

### \*All Material Being Used Shall Conform w/OMWD's Standard Specifications

Project \_\_\_\_\_\_

# PLEASE INDICATE WHICH PRODUCT YOU ARE USING BY PLACING AN "X" ON THE APPROPRIATE LINE TO THE RIGHT OF EACH MANUFACTURER

| BACKFLOW<br>PREVENTER<br>*must be accompanied by<br>a shop drawing | Reduced Pressure Principal Type Assemblies<br>as Approved by the State of California,<br>Department of Health Services   | 15112 | List of Approved Backflow<br>Prevention Assemblies  |
|--|--|-------|---|
| BOLTS AND NUTS<br>316 SS   | Hex-Head Machine, ASTM A193, Grade<br>B8M Bolts and ASTM A194, Grade 8M<br>Nuts  | 15050 | Tripac FastenersPacific Coast BoltITP, Inc  |
| BOLTS AND NUTS, A307   | Hex-Head Machine, Cadmium/Zinc Plated,<br>ASTM A307, Grade B Bolts and A307 2H<br>Heavy Hex Nuts   | 15050 | Tripac FastenersPacific Coast BoltITP, Inc  |
| BURY ELBOW,<br>DUCTILE IRON  | 16" DI Long Radius Bury El, MJ or PO<br>Holiday Free Epoxy Lined Bells   | 15109 |   |
| CASING END SEAL<br>*must be accompanied by<br>a shop drawing       | 1/4" Thick Styrene Butadiene Rubber Sheet<br>End Seal. Use 1" Wide Stainless Steel<br>Bands. Zippered End Seals with Stainless<br>Steel Bands May Also Be Used   |       | Advance Products & Systems          Cascade          Calpico          Pipeline Seal & Insulator          Powerseal          Raychem |
| CASING SPACER<br>*must be accompanied by<br>a shop drawing         | Stainless Steel Casing Spacer, Center<br>Restrained, Position Type with PVC Liner<br>and Non-metallic Anti-friction Runners  |       | Clow  |
| CATHODIC TEST<br>STATION BOX                                       | 54 Lbs Concrete Body with 12 Lb Ductile<br>Iron Lid and Lid Ring. "CP TEST" Shall Be<br>Cast into the Lid in 1" Letters. For Cathodic<br>Protection Test Stations, Anode Ground<br>Beds and Insulated Flange Test Stations | 13110 | Brooks 1 -RT<br>Farwest Type 1-RT<br>J&R 3RT  |
| CATHODIC WELDING   | For Welding Cathodic Bond Wires to Steel<br>Pipelines  | 13110 | Cadweld   |

#### \*All Material Being Used Shall Conform w/OMWD's Standard Specifications

Project \_\_\_\_\_

## PLEASE INDICATE WHICH PRODUCT YOU ARE USING BY PLACING AN "X" ON THE APPROPRIATE LINE TO THE RIGHT OF EACH MANUFACTURER

| COATING, INTERNAL<br>PIPE  | For Coating the Internal Pipe Lining for an Insulated Flange Kit  | 13110                   | Aquatapoxy CCI<br>Hydro-Pox   |
|--|---|-------------------------|---|
| CONNECTOR,<br>TRACER WIRE<br>SPLICING KIT  | All Brass Split Bolt to be Accompanied and<br>Encased with Rubberized Tape, and then<br>Electrical Tape   | 15292<br>15293          |   |
| CORPORATION STOP,<br>MIPT X QUICK JOINT  | Bronze Ball Valve, Male Iron Pipe Thread x<br>Quick Joint (T-Head only), 1", 1-1/2" and 2"<br>Full Opening  | 15080                   | Ford FB1100-x-Q-NL          MCD 74704BQ          Mueller - B25028          Jones - J1935 SG   |
| COUPLING, C900 PVC,<br>HIGH DEFLECTION   | 4" through 12" Solid PVC for Obtaining<br>Deflection Only. Provides 4 Degree<br>Maximum Deflection  | 15292                   | CertainTeed   |
| COUPLING, C900 PVC,<br>CLOSURE / REPAIR  | 4" through 12" Solid PVC for Closure or Repair  | 15292                   | CertainTeed   |
| COUPLING,<br>MECHANICAL<br>CLAMP-TYPE<br>*must be accompanied by<br>a shop drawing | Use for Above Ground DI or Steel Pipe<br>4" or Larger   | 15061<br>15240<br>15251 | Grinnell #7001<br>Tyler 500<br>Victaulic #44, #77   |
| COUPLING,<br>STRAIGHT<br>FLEXIBLE<br>*must be accompanied by<br>a shop drawing     | 4" and Larger, Steel or Ductile Iron<br>Construction, Slip x Slip, Epoxy Coated with<br>304 or 316 Stainless Steel Bolts and Nuts.<br>For Use on AC, PVC, DI, or Steel Pipe | 15122                   | APAC 301          Ford FC1          Powerseal 3501          Romac 501          Smith-Blair 411  |
| COUPLING,<br>TRANSITION<br>FLEXIBLE<br>*must be accompanied by<br>a shop drawing   | 4" and Larger, Steel or Ductile Iron<br>Construction, Holiday Free Epoxy Coated<br>with 304 or 316 SS Bolts and Nuts.<br>For use on AC, PVC, DI, or Steel Pipe              | 15122                   | Ford FC1Powerseal 3501Romac 501Smith-Blair 411APAC 311, 313Ford FC2APowerseal 3501, 3506Romac XR501Smith-Blair 413Romac FlexijointStar - StarFlex |
| <b>DISMANTLING JOINT</b><br>*must be accompanied by<br>a shop drawing              | Telescoping, Adjustable, Double Flanged<br>Fitting, with High Tensile Strength Zinc<br>Plated Tie Bars. NSF-61 Epoxy or Nylon<br>Interior and Exterior Coating              |                         | Romac Flexijoint<br>Star - StarFlex   |

#### \*All Material Being Used Shall Conform w/OMWD's Standard Specifications

Project \_\_\_\_\_

## PLEASE INDICATE WHICH PRODUCT YOU ARE USING BY PLACING AN "X" ON THE APPROPRIATE LINE TO THE RIGHT OF EACH MANUFACTURER

| FIRE HYDRANT,<br>BREAK-OFF RISERS<br>FIRE HYDRANT<br>150 PSI<br>FIRE HYDRANT<br>200 PSI | <ul> <li>Ductile Iron Pipe Spool with Threaded<br/>Flanges, 12" or 18" Long with Machined V-<br/>Groove 4" from One End, Groove to be 1/8"<br/>to 3/16" Deep and ¼" Wide</li> <li>6" Standard 150 PSI Wet Barrel, Bronze<br/>Fire Hydrant, with Six-hole Bolt Pattern.</li> <li>6" High Pressure 200 PSI Wet Barrel,<br/>Bronze Fire Hydrant, with Six-hole Bolt</li> </ul> | 15109<br>15090<br>15109<br>15109 | South Bay Foundry<br>Clow<br>Sigma<br>Star<br>Clow 2060, 2065<br>Jones J3765, J3775<br>American AVK 2464X, 2468X<br>Clow 2060, 2065<br>Jones J3765, J3775 |  |
|---|---|----------------------------------|---|--|
| FITTING, DUCTILE<br>IRON  | Pattern<br>Flanged, Mechanical Joint or Push On,<br>Tees, Bends, Crosses, Reducers, Adapters,<br>etc. For 4" and larger, Per AWWA C110,<br>C111, C153 and OMWD Standards. Holiday<br>Free Epoxy Lined Bells   | 15240<br>15292<br>15293          | American AVK 2464X, 2468X<br>Bachman<br>Sigma<br>Star<br>Tyler<br>US Pipe   |  |
| FLANGE COUPLING<br>ADAPTER  | 6" and Larger, Mechanical x Flange. Steel or<br>Ductile Iron without Anchor Pins, Holiday<br>Free Epoxy Coated, 304 SS Bolts and Nuts.  | 15122                            | Dresser 127, 128<br>Ford FFCA Style<br>Baker 601, 602<br>Powerseal 3521, 3526<br>Romac FCA501, FC400<br>Smith-Blair 912, 913                              |  |
| GASKET, PAPER   | 1/8" Thick Full Face or Ring, Aramid Fiber<br>Bound with Nitrile. No Asbestos Content   | 15050                            | Garlock Bluegard<br>Klinger C4400<br>Tripac 5000<br>Calpico   |  |
| GASKET, RUBBER  | 1/8" Thick, Cloth Inserted Rubber, Full Face<br>or Ring   | 15050                            | Garlock Style 19<br>Tripac 2000<br>Calpico  |  |
| GREASE  | For Bolt Corrosion Protection on Buried<br>Bolts, NO- OX-ID Type  | 15050                            | Sanchem NO-OX-ID<br>Dearborn Chemical   |  |
| GROUT   | Nonshrink Cement Based Construction<br>Grout for Crack Repair, Flooring Mortar,<br>Dowel Grouting, Crack Sealing and General<br>Binding   | 03000                            | UPCON High Flow<br>Master Flow 713  |  |

#### \*All Material Being Used Shall Conform w/OMWD's Standard Specifications

Project \_\_\_\_\_\_

## PLEASE INDICATE WHICH PRODUCT YOU ARE USING BY PLACING AN "X" ON THE APPROPRIATE LINE TO THE RIGHT OF EACH MANUFACTURER

| INSULATING BLANKET<br>*must be accompanied by<br>a shop drawing<br>INSULATING<br>COUPLINGS<br>*must be accompanied by<br>a shop drawing | Insulating Blanket for Corrosion Interference<br>Mitigation<br>Insulating Couplings for Corrosion<br>Protection of Pipelines/Appurtenances                                     | 13110<br>15080                   |   |  |
|---|--|----------------------------------|---|--|
| INSULATING FLANGE<br>KIT  | Insulating Flange Kits for Corrosion<br>Protection of Pipelines/Appurtenances  | 13110                            | Advance Product Systems<br>Calpico<br>Corrpro<br>Farwest  |  |
| JOINT RESTRAINT<br>ASSEMBLY   | 360 Degree Wedge Type Restraint System<br>for Ductile Iron and C900 PVC, Sizes 6"<br>Through 24"   | 15240<br>15292                   | Ford Uniflange 1300 Series<br>Ford Uniflange 1500 Series<br>EBAA Iron<br>Sigma PV-LOK<br>Romac DI - Roma Grip<br>Romac 600 Series<br>Ductile Iron<br>Pipe PVC |  |
| MARKING TAPE  | 6" wide, Warning/Identification (Metallic)<br>Marking Tape for Buried Facilities   | 15061<br>15240<br>15292<br>15293 | Linetec<br>Terra Tape<br>Calpico<br>Christy   |  |
| METER BOX   | 17"x28" Precast Meter Box and 2 Piece<br>Polymer Concrete Cover with Reading Lid<br>for 1" Water Service, Use Purple Covers for<br>Recycled Water                              | 15081<br>15090<br>15091          | J&R Concrete Products, Inc . W5-1/2<br>Armor Cast - A6001420D<br>Old Castle - 1324  |  |
| METER BOX   | 24"x36" Precast Meter Box and 2 Piece<br>Polymer Concrete Cover with Reading Lid<br>for 1-1/2" Water Service, and 2" Water<br>Service, Use Purple Covers for Recycled<br>Water | 15081                            | J&R Concrete Products, Inc . W7<br>Armor Cast - A6001975D<br>Old Castle - 2436  |  |
| OUTLET, WELD-ON<br>*must be accompanied by<br>a shop drawing  | Weld-on Outlet with Reinforcing Collar or<br>Wrapper for Connection to CML&C Steel<br>Pipe   | 15080                            | Pipeline Products   |  |

#### \*All Material Being Used Shall Conform w/OMWD's Standard Specifications

Project \_\_\_\_\_

## PLEASE INDICATE WHICH PRODUCT YOU ARE USING BY PLACING AN "X" ON THE APPROPRIATE LINE TO THE RIGHT OF EACH MANUFACTURER

| PIPE, COPPER WATER<br>TUBE                                      | Type K Soft Seamless Rolled Tubing, Type<br>K Soft Seamless Straight Lengths, Type K<br>Hard Seamless Straight Lengths                  | 15220          | Cerro<br>Mueller<br>Cambridge-Lee  |  |
|---|---|----------------|--|--|
| PIPE, DUCTILE IRON<br>*must be accompanied by<br>a shop drawing | For Water Lines 4" and Larger<br>Manufactured per AWWA C151   | 15240          | American PipeGriffinPacific StatesU.S. Pipe                                    |  |
| PIPE, PVC C900  | For Water Lines 4" through 12"<br>Manufactured per AWWA C900 in Class<br>150 and 200  | 15292          | Diamond Plastics   |  |
| PIPE, PVC C905  | For Water Lines 14" through 24"<br>Manufactured per AWWA C905   | 15293          | Diamond Plastics<br>VinylTech<br>North American Pipe<br>JM Eagle               |  |
| PLASTIC<br>POLYETHYLENE<br>ENCASEMENT                           | 8-mil Thick Polyethylene Encasement Tube<br>for Ductile Iron Pipe, CML&C, and<br>Recycled PVC That is not Already Purple                | 09954          |  |  |
| PLASTIC WRAPPER   | Clear Plastic Wrapper over Wax Tape<br>Coating and Primer in Underground<br>Applications  | 09952          | Denso Tape PVC Self-Adhesive<br>Trenton Poly-Ply                               |  |
| POLYETHYLENE<br>WRAP  | 8-mil Thick Polyethylene Encasement Sheet<br>for Buried Fittings and Valves. Purple Color<br>for Recycled Water                         | 09954          |  |  |
| SERVICE SADDLE<br>FOR ACP, DIP, AND<br>PVC PRESSURE PIPE        | Cast Bronze Body with Stainless Steel<br>Double Band Straps or Single Wide Strap<br>with 4 Bolts, IP Outlet Sizes 1", 1-1/2",<br>and 2" | 15080          | Ford - 202BS<br>Romac - 202BS<br>Jones - J-969<br>McDonald - 3846              |  |
| TAPE, PLASTIC<br>ADHESIVE                                       | 10 to 50 Mil x 2" Wide General Utility Tape<br>for Corrosion Protection of Above and<br>Below Ground Pipes and Fittings                 | 09954<br>09952 | Calpico Vinyl Tape<br>Christy<br>Northtown<br>Polyken - 900<br>Scotchwrap - 50 |  |

### \*All Material Being Used Shall Conform w/OMWD's Standard Specifications

Project \_\_\_\_\_

## PLEASE INDICATE WHICH PRODUCT YOU ARE USING BY PLACING AN "X" ON THE APPROPRIATE LINE TO THE RIGHT OF EACH MANUFACTURER

| TAPPING SLEEVE<br>FOR ACP, DI, AND PVC<br>PIPE<br>THREDOLET<br>TRACER WIRE   | <ul> <li>Fabricated Stainless Steel Tapping Sleeve with Stainless Steel Bolts and Nuts</li> <li>Forged Steel Fitting ASTM A105. 3000#, NPT Threads</li> <li>AWG No. 8 Stranded Copper Wire with High Molecular Weight Polyethylene (HMW/PE) Insulation Specifically Designed for Direct Burial in Corrosive Soil or Water</li> </ul> | 15292<br>15293 | Ford - FTSS<br>PowerSeal - 3460AS<br>Romac - SSTIII<br>Smith Blair - 665<br>Bonney Forge<br>Allied Piping Products<br>Pipeline Products<br>Calpico - HMW/PE #8<br>Farwest - HMW/PE #8<br>KALAS - w-08hmwpe-str |      |
|--|--|----------------|--|------|
| VALVE BOX AND<br>COVERS,<br>MANUAL AIR<br>RELEASE AND BLOW-<br>OFF ASSEMBLIES<br>*must be accompanied by<br>a shop drawing | Cast Iron Frame and Lid and 12" Pipe<br>Sleeve. Cast on the Lid the Words<br>"OMWD", and "WATER" or "RW"<br>(For Street Use Only)  | 15092          | South Bay Foundry - SBF 1243   |      |
| VALVE BOX AND<br>COVERS,<br>GATE VALVE   | Cast Iron Frame and Cover and Extension<br>Pipe. Cast on the Cover the Words<br>"OMWD", and "WATER" or "RW"  | 15101          | South Bay Foundry - SBF 1208-N   |      |
| VALVE,<br>COMBINATION AIR<br>RELEASE &<br>AIR/VACUUM, 3'' AND<br>SMALLER   | Single Chamber, HDPE Control Floats,<br>Stainless Steel Body, 1/4" NPT Test/Bleed<br>Cock  | 15108          | Vent-O-Mat DN25 RBX 2521<br>Vent-O-Mat DN50 RBX 4021<br>Vent-O-Mat DN80 RBX 1631<br>Vent-O-Mat DN100 RBX 2531  | <br> |
| VALVE, GATE,<br>RESILIENT SEATED<br>*must be accompanied by<br>a shop drawing  | 3"- 24" Resilient Seated, Non-Rising Stem,<br>Counter-Clockwise Opening, Type 304 or<br>316 SS Body Bolts, 250 PSI Working<br>Pressure, Holiday Free Interior Lining   | 15101          | AVK or Approved Equal  |      |
| Wax Tape Coating   | 3 Part, Cold Applied Wax Tape Coating<br>System for Buried Piping Components   | 09952          | Denso Densyl Tape<br>Trenton No.1 Wax Tape   |      |